

NASA TM X-73558

(NASA-TM-X-73558) USER GUIDE TO A COMMAND
AND CONTROL SYSTEM; A PART OF A PRELAUNCH
WIND MONITORING PROGRAM (NASA) 29 p HC
A03/MF A01 CSCL 14B

G3/14 Uncias
11459

by Glenn R. Cowgill
Lewis Research Center
Cleveland, Ohio 44135
November 1976



1. Report No. NASA TM X-73558	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle USER GUIDE TO A COMMAND AND CONTROL SYSTEM; A PART OF A PRELAUNCH WIND MONITORING PROGRAM		5. Report Date	
		6. Performing Organization Code	
7. Author(s) Glenn R. Cowgill		8. Performing Organization Report No. E-8999	
		10. Work Unit No.	
9. Performing Organization Name and Address Lewis Research Center National Aeronautics and Space Administration Cleveland, Ohio 44135		11. Contract or Grant No.	
		13. Type of Report and Period Covered Technical Memorandum	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546		14. Sponsoring Agency Code	
15. Supplementary Notes			
16. Abstract <p>The Command and Control task is a portion of the Wind Monitoring Program for the Atlas/Centaur and Titan/Centaur launches managed by Lewis Research Center (LeRC). The wind monitoring system consists of a network operation involving LeRC, Eastern Test Range (ETR) and General Dynamics Corp. of San Diego (GDC) for Atlas launches, and involving the above plus Martin Marietta Corp., Denver (MMC) for Titan launches. Wind data obtained by tracking balloons is sent by electronic means using telephone lines, from ETR to the other three locations. GDC computes steering commands from a system called ADDJUST for the on-board computer and sends this data to LeRC and MMC by telephone. At LeRC these data are received and automatically stored in a micro-processor, then via a real-time program transferred to the UNIVAC 1100/40 computer. At this point the data is available to be used by the Command and Control System. This document describes the use of a set of programs called Command and Control System (CCS). It is intended as a user manual for the operation of CCS by the personnel supporting the wind monitoring portion of the launch mission. A more detailed description of the overall system is available in Ref. 1.</p>			
17. Key Words (Suggested by Author(s)) Computer program; Software; Wind data; Launch wind data; Wind monitor program		18. Distribution Statement Unclassified - unlimited	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages	22. Price*

Abstract

The Command and Control task is a portion of the Wind Monitoring Program for the Atlas/Centaur and Titan/Centaur launches managed by Lewis Research Center (LeRC). The wind monitoring system consists of a network operation involving LeRC, Eastern Test Range (ETR) and General Dynamics Corp. of San Diego (GDC) for Atlas launches, and involving the above plus Martin Marietta Corp., Denver (MMC) for Titan launches. Wind data obtained by tracking balloons is sent by electronic means using telephone lines, from ETR to the other 3 locations. GDC computes steering commands from a system called ADDJUST for the on-board computer and sends this data to LeRC and MMC by telephone. At LeRC these data are received and automatically stored in a micro-processor, then via a real-time program transferred to the UNIVAC 1100/40 computer. At this point the data is available to be used by the Command and Control System.

This document describes the use of a set of programs called Command and Control System (CCS). It is intended as a user manual for the operation of CCS by the personnel supporting the wind monitoring portion of the launch mission. A more detailed description of the overall system is available in Ref. 1.

7

Introduction

The Command and Control task is a portion of the Wind Monitoring Program for the Atlas/Centaur and Titan/Centaur launches managed by Lewis Research Center (LeRC). The wind monitoring system consists of a network operation involving LeRC, Eastern Test Range (ETR) and General Dynamics Corp. of San Diego (GDC) for Atlas launches, and involving the above plus Martin Marietta Corp., Denver (MMC) for Titan launches. Wind data obtained by tracking balloons is sent by electronic means using telephone lines, from ETR to the other 3 locations. GDC computes steering commands from a system called ADDJUST for the on-board computer and sends this data to LeRC and MMC by telephone. At LeRC these data are received and automatically stored in a micro-processor, then via a real-time program transferred to the UNIVAC 1100/40 computer. At this point the data is available to be used by the Command and Control System.

This document describes the use of a set of programs called Command and Control System (CCS). It is intended as a user manual for the operation of CCS by the personnel supporting the wind monitoring portion of the launch mission. A more detailed description of the overall system is available in Ref. 1.

General Description of Command and Control System

Command and control system (CCS) is a set of Fortran programs, symbolic elements consisting of sequences of UNIVAC 1100 series operating control commands and 3 Assembly language programs. CCS is written for and intended to be run on a UNIVAC 1100 series computer with UNIVAC 1100 series operating system, Ref. 2, and UNIVAC 1100 Series Fortran V, Ref. 3.

CCS uses four catalogued files, and initiation of these programs assumes the existence of these files. The four necessary files all use the qualifier LVDSA and have file names COMSYS., W., ST., and either AC. or TC. See the section on description and maintenance of files (p. 23) for detailed information concerning the contents, preparation, and maintenance of all files used within this system.

CCS is intended to be executed from a remote terminal in conversational mode. CCS prompts the user at the terminal to input the name of the task to be executed. After replying, the user will be solicited for the input information necessary to perform the desired task. A detailed description of the possible tasks and all responses is given in the following section, (user's guide). When all information needed to perform the selected task has been input, the program generates the necessary executive controls and also puts into execution the program required to perform this task. Control is then returned to the main program called SYSTEM and the user is prompted to input the next task.

The CCS has been designed to check and validate, as much as possible, the replies to the prompts to catch misspelling of task and data names and to reject erroneous input.

User Guide of CCS

The primary mode of operation is conversational from a remote terminal. This section therefore describes the running of CCS from such a terminal. A secondary mode of operation, (card batch operation), which might be necessary in certain unusual conditions is covered in the section on Anomalies, (p. 25).

In the use of CCS there are 3 phases to be considered 1) logging on, 2) initiallizing the system, and 3) using the system.

1. Logging on

The logon procedure described is the sequence of steps to get logged onto the UNIVAC 1100/40 computer system from a terminal with a PAX telephone and modem setup.

Dial the proper PAX number. When the tone is heard, the data button on the phone is pushed down. Follow the steps indicated on Figure 1, sample logon procedure. The user responses for the procedure are noted with (UR) to the right of the lines. Each input line by the user must be terminated by hitting the key marked RETURN.

```

TTY503                                (UR)

ENTER USERID/PASSWORD:

@@TTY C, CNTL/H      (UR, depress H key while holding down
                      CNTL key, initializes backspace feature)

(RETURN)              (UR)

*DESTROY USERID/PASSWORD ENTRY
*UNIVAC 1100 OPERATING SYSTEM VER. 33.R1A.122T (RSI)*
 @RUN      1323C,YOW6236,LVDSA      (UR)

DATE:  112575      TIME:  161031

```

FIGURE 1 LOGON PROCEDURE

2. Initializing the Command and Control System

After the logon procedure is completed, one input entry is all that is needed to initialize the CCS and get into execution. There are 2 types of launches, (Atlas and Titan), and the command given to initialize will automatically set up the proper analysis program. The 2 possible choices for the input command are:

```
      1) @ADD,P      COMSYS.ATLAS
or     2) @ADD,P      COMSYS.TITAN
```

Again, the input typed into the terminal must be followed by a return. When the initialization procedure is completed the message, 'THIS IS AN ATLAS/A TITAN LAUNCH, TYPE IN DESIRED TASK', will be printed. Figure 2 is a sample of terminal output for an initialization. Note that in figure 2 there is only one line input by the user, denoted by (UR). All remaining lines are output by EXEC8 System denoting that files have been assigned (READY), and various EXEC8 processors are being called upon.


```

@ADD,P      COMSYS.ATLAS      (UR)
@ADD,P      COMSYS,ATLAS
@ADD,P      COMSYS.RUN
READY
READY
READY
READY
READY
FURPUR 27R2 RL72R1 10/28/76 14:02:34
READY
READY
DURPUR 27R2 RL72R1 10/28/76 14:02:37
READY
READY
READY
FURPUR 27R2 RL72R1 10/28/76 14:02:41
END PACK. TEXT=5,TOC=1,SYM=14
END PACK. TEXT=2,TOC=1,SYM=25
READY
READY
MAP28R1 RL71-3 10/28/76 14:02:44 (0,)
END MAP
MAP28R1 RL71-3 10/28/76 14:03:01 (0,)
END MAP
INTERVENING STATEMENTS SKIPPED
FURPUR 27R2 RL72R1 10/28/76 14:03:19
  1 SYM
  1 ABS
CASE UPPER ASSUMED
ED 15.00-10/28/76-14:03:24-(0,)
EDIT
LINES:2 FIELDATA
INTERVENING STATEMENTS SKIPPED
FURPUR 27R2 RL72R1 10/28/76 14:03:25
END PREP.
READY
FURPUR 27R2 RL72R1 10/28/76 14:03:26
END PREP.
READY
READY
  THIS IS AN ATLAS LAUNCH
  TYPE IN DESIRED TASK---POSSIBLE TASKS ARE---
  RUN, PLOT, LIST, DATAIN, STOP, EDIT, EXPRESS, SAVEDATA, SAVEPROGS

```

FIGURE 2 SAMPLE CCS 1. INITIALIZATION

When the last 3 lines shown on Figure 2 are printed, the CCS is in execution, waiting for input data from the user. At this point the required input data is the name of the task the user desires to accomplish. The possible tasks are described in the next section.

3. Using the Command and Control System

All task names and their associated input data must be typed on the keyboard with no initial spaces and no embedded spaces.

Input data to CCS is verified by the program before the next data is requested. If an error is detected a message will be printed on the terminal and the user will be prompted for a correction. If typing errors are detected before the return is given they may be corrected, by either backspacing or by eliminating the entire line and starting again at the beginning of the line. To backspace, if there is no backspace key on the terminal, for example as on the TI Silent 700 terminal, depress the key marked CTRL and then hit the H key as many times as positions desired to backup. For example, if it is desired to back space 4 positions depress and hold CTRL key down, then hit the H key 4 times. (This backspace feature must be initialized, see Figure 1). To eliminate the line to start over hold the CNTL key down then the X key. This will return the printer to start position without transmitting any data to the computer.

The list of the available task names along with a short description of each follows.

<u>Taskname</u>	<u>Description</u>
RUN	initiate execution of the preselected trajectory program
PLOT	produce plots of a set of wind data
LIST	produce a list of a set of data, or a list of names of data available
DATAIN	move data from the micro-processor into the computer
EXPRESS	execute the analysis program using the most

recent wind and steering data. Most recent means by year, month, day, and time of day in the name of the data set.

EDIT	edit or change some values of a set of wind data or steering data
STOP	used to stop execution of CCS and return control to the UNIVAC Executive System
SAVEDATA	update the magnetic tape which contains the historical data records, as well as the contents of the current files
SAVEPROGS	update the magnetic tape which has a record of all program files

Described below are the responses by user to successfully complete each of the above tasks.

RUN - When the RUN task is requested the user will be prompted by the system for the following input data:

- 1) Name of wind data to be used.
- 2) Name of steering program. If library steering programs are required it is necessary to input two names, one for pitch program and one for yaw program. When the prompt for steering name is made by the system the user may input either the pitch name or the yaw name. After the input name has been verified the program will then prompt the user for the other steering name.
- 3) At this point the data values, called namelist input, are printed on the terminal along with a prompt as to whether the user wishes to change any of these values. The correct responses are Y for yes and N for no.
- 4) If the response from 3) is Y the user will be prompted for the name of the variable he wishes to change then after this name has been verified, he will be prompted for the new data value. After entering the new data value the user will then be prompted to answer Y or N to the question, "Any more change?". Values may be altered for any number of the namelist variables during this step.

An answer of N completes this portion of the input data.

- 5) The next input data for the RUN task is mode of running the analysis program. Two modes are available, Demand or Batch. Demand mode means that the analysis program is immediately started with the condensed output printed at the terminal. Hence the terminal is in use during the entire length of the run. In Batch mode the analysis program is started in core as if the run were submitted to the computer via cards. All of the output goes to the high speed printer in the computer room. Hence, as soon as the run is started the terminal is not being used by that particular analysis run, and the user can then request another task to be done. Any number of runs may be started in batch mode as fast as the user can input the necessary input data. However experience has shown that starting a number of batch runs seems to slow down the execution time of all of them. It is recommended that usually not more than one or two batch runs be started to run concurrently at any given time.

PLOT - Input for the plot task calls for four pieces of data.

- 1) Name of wind data to be plotted
- 2) Value of the launch azimuth in degrees.
- 3) C, T, or N - The vectors to be plotted may be saved on cards--C--, tape--T--, or not saved--N.
- 4) T or P - where should the plot output be printed?
 T - on users terminal
 P - on the high speed printer

LIST - When the list task is requested, a message will be printed on the terminal 'LIST WHAT'. The possible responses to this prompt are as follows:

WNAMES - list names of wind data in file W.

SNAMES - list name of steering data in file ST.

ALLNAMES - list names of all sets of data in both W. and ST. files.

DATA - list the values of a set of data. User will be prompted for the name of the data set he wishes to list.

LATESTNAMES - print out the names of the most recent wind data and most recent steering data. Most recent determined by the time, day, month, and year in the data set name. See section on naming of wind and steering data.

LATESTDATA - print out the values of the most recent wind and steering data.

DATAIN - On a signal from the microprocessor operator, type the command DATAIN. This starts into execution the real-time program (JPGM) which moves the data from the micro-processor into the computer. This program then makes a determination as to the type of data, i.e. wind data or steering data, then generates the data set name according to the naming conventions described in the section on data naming and formats, then moves the data into the proper data file, W. or ST.

EXPRESS - The express task runs the trajectory analysis program using the latest wind and steering data. The only input prompts for the express task are those to change the namelist input data. The analysis program is automatically executed in demand mode.

EDIT - The edit task permits the user to edit, change or correct, any data value or values in a set of data. The necessary input data for which the user is prompted are:

1. Name of the wind or steering data.
2. Line number of the data set which contains the value to be changed. The header card is line number 1.
3. Which element of the specified line is to be changed, by number, counting left to right, starting with the column containing actual data values.
4. The new data value. For wind data 3 digits must be input. For steering data 10 characters must be input, (sign; 6 digit mantissa; sign and 2 digit exponent)

Note-all sets of wind data may be edited using this task, but only ADDJUST steering data (p. 18) in "new" format may be edited with this task. Steering data in "old" format and library steering data may not be edited using this task. Types and formats of steering data are discussed on pages 17 and 18.

STOP - The stop task returns control to the UNIVAC operating system (EXEC8) command language. This task is used when a launch exercise has been completed and no further tasks are required. The STOP task may also be used in case of trouble in order to recover from an error by the use of UNIVAC control commands. The user then would restart execution of CCS by typing in the following (XQT bbbb .SYSTEM).

SAVEDATA - As described above this task updates the magnetic tape containing the historical records of the data. No further input responses are required. This task is normally done upon completion of a launch to archive the data.

SAVEPROGS - As with the previous task no other input responses are prompted for. This task would normally be called prior to a series of testing for a launch in order to have the most recent symbolic elements and also the most recent frozen versions of the programs on a magnetic tape as a back up in case of a disk failure.

As each task, except for the stop task, is completed the CCS returns to the main program and requests a new task name to be input by the user.

As described above, the CCS prompts the user for necessary data to perform the requested task. At any of these prompts the user may omit the execution of the selected task by typing STOP instead of the required data. This will stop the prompting for input for that task and return to the main program and type the message "TYPE IN DESIRED TASK---", requesting that a new task name be input.

A typical launch exercise consists of 4 cycles. In each of the first three cycles three sets of data are received, two wind data sets from ETR, a Windsonde and a Jimsphere, and one steering program from GDC computed from the Windsonde.

These three cycles occur approximately five hours, three hours and one hour prior to the scheduled launch time. The sequence for the first cycle is normally as follows. 1) Receive Windsonde data from ETR into the microprocessor. Perform the CCS commands DATAIN, PLOT. 2) Receive Jimsphere data from ETR, do DATAIN, PLOT. 3) Run the Windsonde data with a few library steering programs chosen by the Wind data director. 4) Receive the steering program from GDC, run this steering data with both winds received.

For all subsequent cycles, 1) Receive Windsonde data, do DATAIN, PLOT, RUN with steering data from previous cycle. 2) Receive Jimsphere data, do DATAIN, PLOT, RUN with previous steering data. 3) Receive new steering data, RUN with both Wind data sets. Cycle four is a contingency cycle and Windsonde data only is usually received and plotted. Under normal conditions the contingency cycle is received only minutes prior to launch, and so this data is run only if a hold condition exists to delay the launch.

In between cycles there is usually about an hour of inactivity. During this period of time Computer Operations should be notified so other programs can be run. The CCS is waiting for input data during this period of time. During the periods of inactivity the executive system will print a message, "TIMEOUT WARNING", after a ten minute period of inactivity. If during the next ten minutes following the warning there is no input from the terminal the phone line will be dropped by the executive system. To keep this from happening whenever the timeout warning message is printed the operator should depress the return key. This is enough input so that the system will stay on line.

When the launch exercise is completed type in STOP for the task name. When the STOP task is requested a message will be printed "STOPPING---". When FIN is typed in the user is logged off the computer and some accounting lines will be printed. When all of the accounting lines are printed the user should type in @@TERM. This will disconnect the phone line to the computer. See figure 3.

```

THIS IS A TITAN LAUNCH
TYPE IN DESIRED TASK---POSSIBLE TASKS ARE---
RUN, PLOT, LIST, DATAIN, STOP, EDIT, EXPRESS, SAVEDATA, SAVEPROGS
LIST (UR)
LIST WHAT, (WNAME, SNAME, ALLNAME, DATA, LATESTNAME, LATESTDATA)
WNAME (UR)
WTD000000000
WTD200000000
WSD211720085
JIM213720085
WSD180725095
JIM181725095
WSD195225095
JIM200124095
WSD215225095
JIM220225095
WSD225225095
RND000226095
WSD001226095
JIM003126095
WRD000000000
TYPE IN DESIRED TASK---POSSIBLE TASKS ARE---
RUN, PLOT, LIST, DATAIN, STOP, EDIT, EXPRESS, SAVEDATA, SAVEPROGS
EDIT (UR)

TYPE IN NAME OF DATA TO BE EDITED
STOP (UR)

TYPE IN DESIRED TASK---POSSIBLE TASKS ARE---
RUN, PLOT, LIST, DATAIN, STOP, EDIT, EXPRESS, SAVEDATA, SAVEPROGS
STOP (UR)
S PING
@MSG,N END OF PROGRAM ENTER @FIN.
@FIN (UR)
RUNID: 1323C ACCT: YOW6236 PROJECT: LVDSA
TIME: TOTAL: 00:01:00.891
CAU: 00:00:01.843 I/O: 00:00:18.116
CC/ER: 00:00:40.932 WAIT: 00:01:36.607
SRC: PS -- 12538 ES -- 4200050
START: 11:52:33 DEC 01,1975 FIN: 11:55:58 DEC 01,1975
*TERMINAL INACTIVE*
@@TERM (UR)

```

FIGURE 3 SAMPLE OF A LIST TASK, STOP, AND LOGOFF

Naming and Format of Wind and Steering Data

Naming

The Wind and steering data names are generated by the real-time program, then put into the proper data file, W. or ST. The names are made up from information on the first record of each set of data, denoted as the header card, by the following conventions. All names are 12 characters in length.

For wind data the name is made up of 3 alphabetic characters indicating the type of tracking used, followed by 9 numeric characters designating the balloon release time (4 digits), day (2 digits), month (2 digits), and year (1 digit). The balloon release time is given as Greenwich Mean Time (Z). See figure 4 for typical wind data names, type of tracking, and a typical header card.

<u>Typical Wind Names</u>	<u>Description</u>
WSD132523085	Windsonde released at 1325 hrs Z on August 23, 1975
JIM220225095	Jimsphere released at 2202 hrs Z on September 25, 1975
RND204620085	Raywindsonde released at 2046 hrs Z on August 20, 1975

Typical Header Card (Numbers indicate card columns)

1	10	20	30	40	50	58
C J	,0031Z	26 09 75,	ETR WIND DATA,	3072,	ALT 200 F,	VEL FPS

FIGURE 4 Typical Wind Names and Wind Header Card

The names of ADDJUST steering program data are also made up of 12 characters. The alphabetic character A, followed by 11 numeric characters designating steering program ID (2 digits), time (4 digits), day (2 digits), month (2 digits), year (1 digit). The time, day, month, and year will match the time, day, month and year of the wind data that was used to design the steering data.

The library steering programs are broken into two groupings. Sets of data for pitch programs and sets of data for yaw programs. The data sets for pitch have P as the first character of the name, followed by 11 alphabetic and numeric characters for identification. The yaw data sets begin with the letter Y, again followed by 11 characters. See figure 5 for typical steering names and a header card from an ADDJUST data set.

A05132523085	ADDJUST steering program
PlH050A0A36A	Library pitch steering
PlT100A0A36A	
YlR050A0A36A	Library yaw steering
YlL100A0A36A	

1	10	20	30	40	50	60	70	80			
C	PY	,2152Z	25	09	75,GDC	STEERING	NO.	11	PlA1100*AC36	YlA1100*AC36	__115533

FIGURE 5 Typical Steering Data Names and a Steering Header Card

Format:

There are two formats for the wind data and two formats for the steering program data, to be designated as "old" and "new". For wind data the old format has 18 values per card. Input format is (8X,18(I3,1X)). New format has 16 values per card plus checksum information in CC 72-80. CCS reads these data with format (8X,16(I3,1X)). The header card on the wind data, both old and new formats, must contain the altitude interval in cc 45,46,47,48 and the units of distance in cc 50. See sample header card in figure 4. The CCS automatically determines which format to use and reads the data in with the proper format. Hence the only restrictions on the wind data, for either old or new format, are that there must be a header card and the header card must have at least the two pieces of information described above in cc 45 to 48 and in cc 50.

There are 3 types of steering data. ADDJUST steering in "new" format, ADDJUST steering in "old" format and library data. The library steering data and "old" format data are read in namelist format and hence the data must be in a form that is readable by namelist input. Further the old format data sets and library data sets must not have a header card.

Recall that the time, date and year is part of the data set names for the steering data. Any steering data whose name has a date prior to July 1, 1975 is automatically called "old" format by CCS.

The steering data in new format, i.e. any name with date on or after July 1, 1975, is read by the programs with a formatted read. This format is (6X,6E10.6/6X,5E10.6). CC 72-80 contain checksum information.

Examples of Wind data, ADDJUST steering data, and library steering data in both new and old formats are shown in figures 6,7,8,9,10,11. Note that in figure 8, steering data in new format, there are no decimal points. The decimal point is implicitly in front of the first digit. For example from figure 8 the first data value is shown to be 217029E-14, this is read by the program as 0.217029E-14.

```

C J      ,2243Z 13 05 76,ETR WIND DATA 2211,ALT 230 F,VEL FPS      000022
A 001    140,136,134,131,129,133,136,134,130,137,136,147,149,153,146,145, 116611
A 017    150,157,154,153,158,161,165,165,159,163,153,148,150,151,156,151,YV117733
A 033    142,143,147,143,152,151,146,160,156,141,150,137,142,148,146,138,II116677
A 049    137,121,123,129,144,162,186,188,193,174,167,210,170,175,185,178,...116666
A 065    175,194,190,179,181,194,183,185,193,190,206,222,214,212,221,218,22116611
A 081    227,239,232,238,241,244,237,244,241,243,246,255,247,253,260,255, 117777
A 097    261,256,268,263,258,264,256,262,257,263,263,269,258,258,256,254,LL116644
A 113    254,253,258,258,258,263,264,270,267,263,268,268,263,272,277,273,AA117733
A 129    272,276,283,283,291,292,294,291,295,304,306,310,315,307,302,297,33117711
A 145    302,299,307,309,303,298,299,308,300,296,297,303,296,304,302,299, 117755
A 161    305,298,303,298,303,304,308,303,308,301,307,303,300,299,298,301,XX116600
A 177    296,307,304,313,309,308,312,308,296,301,301,304,302,299,306,299,**117733
A 193    301,292,295,295,289,283,269,275,275,283,280,284,280,283,281,283,PP117722
A 209    283,282,277,275,272,270,272,273,269,267,265,264,272,272,285,289,00117711
A 225    294,302,306,299,298,297,296,297,306,310,316,322,321,315,315,313,00116622
A 241    311,311,314,306,299,302,302,309,312,317,323,327,330,325,321,314,00117766
A 257    321,324,326,324,315,310,297,000000000000000000000000000000000000, 117777
S 001    027,030,032,035,036,043,043,043,043,042,041,037,039,039,039,036,00115566
S 017    034,034,026,023,024,022,024,025,027,028,028,026,024,022,024,027,:114433
S 033    026,020,026,024,021,024,019,018,021,018,015,018,014,020,014,015,**114422
S 049    012,008,011,009,007,012,009,010,011,010,005,006,007,009,015,018,**114411
S 065    018,016,020,018,017,014,015,014,011,010,011,014,020,017,025,029,**115533
S 081    028,029,031,029,029,028,028,028,026,029,026,030,031,031,028,030,LL114422
S 097    030,032,027,028,028,027,028,031,034,040,037,039,041,042,042,046,KK115555
S 113    045,051,048,049,051,054,051,051,054,050,050,049,047,040,040,042,00115500
S 129    040,037,036,037,037,036,036,036,034,034,035,037,037,037,034,035,XX115522
S 145    033,034,035,037,038,036,034,033,036,033,032,033,032,031,031,030,77115511
S 161    030,029,031,029,029,027,028,030,030,036,034,036,038,038,037,037,00114477
S 177    036,032,033,030,029,030,028,027,033,031,032,030,030,035,032,023,22114466
S 193    029,031,027,028,029,028,031,033,036,038,040,039,041,042,042,041,KK115555
S 209    043,044,042,046,050,048,045,047,048,046,047,045,047,045,042,042, 115566
S 225    050,054,057,052,054,057,059,065,076,080,082,076,077,077,069,063,:114433
S 241    059,054,050,048,044,042,044,045,046,053,058,063,061,060,053,047,YV115577
S 257    045,042,037,030,031,031,027,000000000000000000000000000000000000, 114466

```

FIGURE 6 Sample Wind Data "New" Format

ORIGINAL PAGE IS
OF POOR QUALITY

TEST WIND DATA IN OLD FORMAT , TITAN TEST 200 F ALT=200. UNITS=F

A(001)=310,328,335,339,342,345,348,351,357,359,010,015,354,348,342,339,339,340,
A(019)=336,339,339,332,333,318,318,315,312,310,305,305,303,302,300,298,302,295,
A(037)=301,301,303,305,301,303,305,301,306,309,319,320,328,327,326,321,320,317,
A(055)=312,309,307,309,308,314,314,318,323,329,332,331,327,326,328,328,324,328,
A(073)=325,329,330,330,332,330,332,329,326,319,314,312,308,305,302,299,297,296,
A(091)=289,291,290,288,285,285,283,283,282,282,284,284,287,288,288,287,286,286,
A(109)=287,287,287,282,283,283,281,282,280,281,281,279,276,275,275,274,273,272,
A(127)=273,273,273,273,275,275,275,275,277,277,277,278,279,281,281,281,281,281,
A(145)=281,280,281,282,281,281,282,282,281,282,280,280,278,277,275,273,272,271,
A(163)=269,269,269,269,269,269,269,268,267,266,265,264,264,264,263,263,263,261,
A(181)=261,260,260,261,261,261,263,263,263,264,265,266,267,267,267,269,270,271,
A(199)=273,271,272,271,268,266,266,265,267,267,266,265,265,264,263,266,267,270,
A(217)=272,272,273,271,271,273,275,277,276,275,277,277,276,276,276,277,273,273,
A(235)=272,269,269,268,267,271,269,271,273,273,278,273,276,273,279,277,276,273,
A(253)=267,267,270,272,273,277,277,272,278,276,276,278,272,273,270,270,270,270,
A(271)=265,266,266,269,268,269,269,271,273,269,268,262,256,261,0000000000000000,
S(001)=010,020,029,031,033,035,035,038,036,035,035,033,037,028,029,028,028,024,
S(019)=034,031,040,038,036,034,035,041,038,042,041,042,042,049,046,049,051,053,
S(037)=054,053,055,059,051,060,054,053,050,048,051,055,053,067,070,077,076,077,
S(055)=080,074,080,073,073,066,067,061,064,066,071,077,076,076,075,074,075,066,
S(073)=068,067,066,067,068,069,067,068,069,064,065,065,063,072,066,069,071,068,
S(091)=077,081,083,089,091,095,099,097,102,100,103,104,111,112,112,122,121,130,
S(109)=133,130,123,123,127,128,130,130,127,127,124,125,122,125,131,133,134,137,
S(127)=141,143,142,144,147,147,145,147,149,149,148,149,150,151,150,151,147,147,
S(145)=151,149,150,153,151,151,154,154,154,157,156,156,160,161,160,164,161,167,
S(163)=165,164,162,164,163,163,164,165,165,167,167,165,166,168,171,173,172,169,
S(181)=172,172,172,175,175,173,176,174,172,172,169,159,172,172,172,176,172,174,
S(199)=175,172,171,165,159,154,150,145,145,148,145,145,146,147,147,150,152,149,
S(217)=149,149,146,147,145,144,146,143,138,139,137,131,130,130,126,122,124,121,
S(235)=118,117,120,121,120,121,127,128,129,130,129,125,121,122,121,116,114,114,
S(253)=112,111,108,109,111,107,105,107,106,102,100,101,105,107,108,112,112,115,
S(271)=114,115,113,108,102,105,100,095,093,092,083,079,082,086,0000000000000000,

FIGURE 7 Sample Wind Data "Old" Format

FINAL PAGE IS
OF TOTAL QUALITY

```

C PY .17392 22 07 76,GDC STEERING NO. 12      P1A1200*AC40 Y1A1200*AC40 115522
P2= 217029-14,-329625-15, 154396-15, 187773-15,-397789-15, 471382-15,CC117711
506603-15,-215628-15, 436934-16, 444426-16, 138048-16, 00001122
P1= -449835-10,-165724-10,-185686-10,-140967-10,-123133-10,-160025-10, 116600
-110819-10,-410961-11,-768077-11,-563747-11,-366869-11, 99001177
P0= 157380-05, 136530-05, 121163-05, 107296-05, 995138-06, 923627-06,AA117755
855399-06, 812654-06, 786715-06, 714277-06, 619305-06, RR000022
Y2= -144759-14, 875707-15,-312234-15, 220413-15,-486703-15, 530968-15,>>116666
501339-15,-316456-15,-740161-16, 231484-18, 130111-18, 77000055
Y1= 123966-10,-830498-11, 160514-11,-143368-11,-116192-13,-638041-11,--117711
363196-12, 453788-11, 110967-11,-303037-13,-257705-13, 66000011
Y0= 0, 173004-07, 690580-08,-236050-09,-903260-09,-131289-07,##115555
-317568-07,-174148-07,-263683-08, 135824-08, 544761-09, --000011

```

FIGURE 8 Sample Steering Data "New" Format

```

P2( 1)= 2.65819068E-09, 4.11470771E-10, 2.54507930E-11,
P2( 4)= -8.40135596E-11, 9.68033925E-10, -5.09382659E-10,
P2( 7)= 3.45913878E-10, -1.04141752E-10, 1.23916544E-10,
P2(10)= 6.57678393E-11, 1.36696724E-11,
P1( 1)= -4.92013033E-05, -2.62073733E-05, -1.45055879E-05,
P1( 4)= -1.32189348E-05, -1.52389575E-05, -4.76476597E-06,
P1( 7)= -1.21227345E-05, -7.72851656E-06, -8.91743263E-06,
P1(10)= -6.38971937E-06, -3.60039004E-06,
P0( 1)= 1.57079633E+00, 1.35915904E+00, 1.17583418E+00,
P0( 4)= 1.06141833E+00, 9.79080231E-01, 9.27086292E-01,
P0( 7)= 8.90527896E-01, 8.38562070E-01, 7.97315943E-01,
P0(10)= 7.20533272E-01, 6.19046020E-01,
Y2( 1)= -1.61109142E-09, 3.53516543E-10, -1.40591339E-10,
Y2( 4)= -1.59039875E-11, -5.77321235E-11, 2.14335246E-10,
Y2( 7)= 5.66881841E-10, -5.35005635E-10, -1.30507886E-10,
Y2(10)= 2.50408942E-11, 1.03868933E-13,
Y1( 1)= 1.37968323E-05, -3.52581824E-06, 5.15760356E-09,
Y1( 4)= -1.64073177E-06, -2.34852287E-06, -3.54915533E-06,
Y1( 7)= -7.70317181E-09, 3.78654047E-06, 1.95369797E-06,
Y1(10)= -2.22789240E-07, -2.19770872E-08,
Y0( 1)= 0, 1.92487002E-02, 1.36672130E-02,
Y0( 4)= 4.71062810E-03, -5.70630608E-03, -1.88922235E-02,
Y0( 7)= -3.12796190E-02, -1.71460889E-02, -1.15885274E-02,
Y0(10)= -5.10233632E-03, 4.58236577E-04,

```

FIGURE 9 Sample Steering Data "Old" Format

P0(01)= 1.57080E+00, 1.37506E+00, 1.19986E+00, 1.06538E+00, 9.81355E-01,
 P0(06)= 9.19575E-01, 8.65579E-01, 8.20962E-01, 7.82441E-01, 7.17076E-01,
 P0(11)= 6.19766E-01,
 P1(01)= -3.82558E-05, -2.48851E-05, -1.88542E-05, -1.49769E-05, -1.30621E-05,
 P1(06)= -1.19003E-05, -9.92232E-06, -8.14813E-06, -7.24028E-06, -5.78083E-06,
 P1(11)= -3.56236E-06,
 P2(01)= 1.39147E-09, 3.73155E-10, 2.55447E-10, 1.62261E-10, 1.41207E-10,
 P2(06)= 2.20224E-10, 1.99798E-10, 8.87724E-11, 7.03774E-11, 4.57653E-11,
 P2(11)= 1.28672E-11,

FIGURE 10 Sample Library Steering - Pitch

Y0(01)= 0, -6.66117E-02, -3.53190E-02, 3.77615E-03, 3.23979E-02,
 Y0(06)= 5.50226E-02, 7.00590E-02, 6.57137E-02, 5.51313E-02, 3.49821E-02,
 Y0(11)= -1.07129E-04,
 Y1(01)= -4.81621E-05, 2.76728E-06, 4.83674E-06, 4.88151E-06, 4.65661E-06,
 Y1(06)= 5.50062E-06, 1.43840E-06, -2.13696E-06, -2.09425E-06, -1.95391E-06,
 Y1(11)= 8.10218E-09,
 Y2(01)= 5.63333E-09, 1.43110E-10, 6.26888E-12, -1.85361E-11, -2.63354E-11,
 Y2(06)= -4.98665E-10, -4.61493E-10, 4.09415E-12, 7.93381E-12, 9.97751E-12,
 Y2(11)= -4.66117E-14,

FIGURE 11 Sample Library Steering - Yaw

File Description and Maintenance

As mentioned earlier (p. 5) four files are used during the execution of CCS. Two of these four files are the data files W. and ST. which contain the sets of wind data and steering data respectively. These two files are catalogued public. The maintenance of these two files is quite simple. Prior to a sequence of exercises leading up to a launch it is best to purge the wind data from file W. except for one or two sets to be used as testing data. The ST. file should also be purged except for one test data set. Then insert into file ST the steering libraries that will be used during the up-coming launch. This is accomplished by UNIVAC EXEC8 control language. Other files that may be used in this operation are ACLIB. or TCLIR. (which are files containing library steering programs for ATLAS and TITAN respectively). Figure 12 shows two possible sets of EXEC commands: one to purge and save two elements of file W.; the other to purge and save one element from ST., and then store Titan libraries in ST.

PURGE W.

- 1) Usual logon procedure; Dial up, TTY503, @RUN ----, etc.
- 2) @ASG,T SAVEW,F///200
- 3) @COPY,S W.WTD000000,SAVEW.WTD000000 (moves 2 wind data)
- 4) @COPY,S W.WSD215225095,SAVEW.WSD215225095 sets into SAVEW.)
- 5) @ERS W. (erases file W.)
- 6) @COPY,S SAVEW.,W. (moves the 2 data sets
- 7) @FIN back into W.)

PURGE ST.

- 1) Logon as above
- 2) @ASG,T SAVEST,F///200
- 3) @COPY,S ST.A11215225095,SAVEST.A11215225095 (moves 1 ST data
- 4) @ERS ST. set to the save file)
- 5) @COPY,S 1CLIB.,ST. (moves TITAN steering libraries into ST.)
- 6) @COPY,S SAVEST.,ST. (moves saved data set back to ST.)
- 7) @FIN

These operations may be combined with a single LOGON and fin.

FIGURE 12 Sample Univac Executive Commands to Save Some Data, Purge Files W. or ST., restore saved data into the files., then to store a set of library steering programs into ST.

At the end of a launch it is recommended that the task SAVEDATA be requested from CCS. This will update tape 0341, (data tape), by saving the current contents of files W. and ST., merge new wind data and new steering data with historical data and save the steering library files ACLIB and TCLIB on the tape. After doing SAVEDATA at the end of a launch, the user may now go through the purge procedure to get ready for the next exercise.

The third of the four files used by the CCS is a file named COMSYS. COMSYS is catalogued public in read-only mode, and contains the CCS programs and runstreams necessary to execute CCS. This file is built and maintained by Computer Services Division personnel.

The fourth file used is either the file AC., (Atlas program), or TC. (Titan Program). These files are built by the commands:

```
      @ADD      COMSYS.FREEZEATLAS
or      @ADD      COMSYS.FREEZETITAN
```

These two commands build the files AC or TC by forming the executable elements. The programs used to build these executable elements are the relocatable (binary) versions of the Atlas or Titan programs which reside in the two catalogued files named ATLAS. and TITAN. respectively. The ATLAS. and TITAN. files are maintained by LVD personnel.

After all programs are in the form desired for an upcoming launch, and before the exercises begin it is suggested that the task SAVEPROGRAMS be executed from CCS. This will save all of the program files on magnetic tape U0267 to be available if the computer system loses the files resident on the disk, so that recovery of the programs in frozen form is possible.

Anomalies

While using CCS over a period of time occasional unusual circumstances have arisen and occasional errors have occurred. Following is a list of these circumstances along with possible correction methods. This list is not exhaustive nor does it cover all possible anomalies.

- 1) If the real time program cannot generate a data name from the header card of the set of data, the

data set is saved in a file called ERR. The element name given to the data set is the current date and time. When this occurs an error message is printed on the terminal and the element name will appear on the line containing ELT ERR. date time. To recover from this it is necessary to request the STOP task from CCS. This will turn control over to UNIVAC EXEC. Then by using EXEC commands the header card can be corrected, then the element may be renamed according to CCS naming conventions and then moved to the proper data file, W. or ST., to be used by CCS. If an error of this type occurs it is a good idea to list the data set to check for other errors in the data as far as can be determined. After the data has been moved into the proper file and determined to be useable by CCS it is necessary to restart execution of CCS. This is done by the control XQTbbSYSTEM.

- 2) If the real time program senses a card count different than that transmitted to the micro-processor a message will be printed to that effect. The data is stored in the proper data file however. It is a good idea to list this data.
- 3) If the phone line to the CCS terminal drops, hang up, redial, and reinitialize to resume running.

If the phone at micro-processor drops, the CCS operator must stop execution of the program by @X T. The micro-processor operator must reinitialize the micro-processor then redial. The CCS operator then gives the DATAIN task again.

- 4) Occasionally the program appears to stop executing, or be holding. The symptoms of this is no output to the terminal when it is expected for some period of time. Two minutes is a reasonable time to wait. If this occurs just hit the return key. This will normally get things started again, or a message will be printed giving current status.
- 5) It may be desirable to change the value of one or more of the namelist variables for the duration of the time on the computer. This would eliminate the need to make the change each time the run task

is requested. This can be done with the use of EXEC commands, primarily the text editor. To make such a change first request the CCS task STOP. Then @ED,Ubbbbbl5.. This will invoke the text editor, at which time the changes can be made. Should there occur a need to reinitialize the CCS after such a change is made, it will be necessary to remake the changes as they are lost during the reinitialization process.

- 6) To send messages to the computer operator at the console, type the following @@MSGb YOUR MESSAGE (50 characters or less).
- 7) If it should become necessary to stop the execution of a task, this can be done by hitting the BREAK key followed by XbT. This will terminate execution of the task in progress. However any output which has not as yet been printed will print out before control is returned to the terminal.
- 8) The CCS can be run from cards in a batch mode in 2 ways. Normally the only tasks that would be done using cards are PLOT,RUN, and DLTAIN. In order to put wind or steering data into the data files from cards the user needs the deck of data cards and three executive control cards. The deck set up for wind data is as follows:

```
@RUN,M          1323C,YOW6236,LVDSA
@ELT,IS          W. data name
```

data deck

FIN

To plot or run analysis programs by using cards the CCS can be put into execution; then the input to perform the tasks would be on cards, one input per card. Figure 13 shows a sample run stream to plot a wind data set then run the Atlas analysis program twice. To run Titan programs substitute TITAN in place of ATLAS on the second card.

@RUN,M	1323C, YOW6236, LVDSA
@ADD,P	COMSYS.ATLAS
PLOT	Plot wind data RND000226095
RND000226095	
100.982	
P	
RUN	Run atlas program with wind
RND000226095	RND000226095 and steering
A11215225095	A11215225095, no changes of
N	any namelist data
DEMAND	
RUN	
WSD001226095	
A11215225095	
N	
DEMAND	
@FIN	

FIGURE 13 Sample of Deck Setup to Plot and Run
Analysis Programs with Cards

Another way of plotting and running from cards is as follows:

To Plot	@RUN	1323C,YOW6236,LVDSA	
	@ADD,P	COMSYS.PLOTTCCARDS	
	@ADD,P	.WSD183509095	
		100.986	
	@FIN		
To Run	@RUN	1323C,YOW6236,LVDSA	
	@ADD,P	RUNTCCARDS	
		NOMINAL=.FALSE., RSAFTY=1.,	change namelist data
	\$END		
	@ADD,P	.A08084621075	steering name
	@ADD,P	.JIM084507215	wind name
	@FIN		

REFERENCES

1. Goldberg, Fred: Wind Data Network Communication System.
NASA TM X- , 1976.
2. UNIVAC 1100 series operating series, Programmer Reference.
UP-4144, Sperry Rand Corp., 1973, rev. 3.
3. UNIVAC 1100 series FORTRAN V Programmer Reference. UP-4060,
Sperry Rand Corp., 1973, rev. 2

APPENDIX A
LOGICAL FLOW DIAGRAM OF CCS

